



HASSELBLAD LUMBER SALES

2101 N. Pearl Street, Suite 301
 Tacoma WA 98406
 Phone 253-752-6123
 Fax 253-752-6282

NHLA HARDWOODS FOR CONSTRUCTION BOXED HEARTS & PLANKING GRADE HIGHLIGHTS

	<u>SELECT CAR STOCK</u>	<u>COMMON DIMENSION</u>	<u>SOUND SQUARE EDGE</u>
WANE: Timbers	On any 1 face, limit to 2 corners up to 1/4 of aggregate width	On any 1 face, limit to 2 corners up to 1/4 of aggregate width	On 1 or more corners up to 1/3 of aggregate of width or thickness
WANE: Planks: 5" thick or less.	Up to 1/3 of width, - thickness & length Maximum wane allowed on 20% of pieces	Up to 1/3 of width, thickness & length Maximum wane allowed on 30% of pieces	Same as timbers No limit on maximum
SOUND KNOTS	Less than 1/2 face allowed 1 per foot Less than 1/6 face are not limited	Up to 1/2 of face allowed 1 per 6 ft Up to 1/3 face are not limited	Sound knots are admitted without limit
UN SOUND KNOTS & HOLES	Limit 1 per 6 feet, up to 1 1/4"	Limit 1 per 4 feet, up to 1 1/2"	Occasional unsound knots and holes permitted if they do not go through timber.
PITH:	Limit 1/3 of 1 face exposed. No limit if boxed	Limited to 1 face exposed. No limit if boxed	Admitted boxed or showing, without limit
RING SHAKE:	Up to 2 rings in boxed heart, entire circumference	Up to 4 rings in boxed heart, entire circumference	Up to 6 rings in boxed heart, entire circumference
SURFACE SHAKE:	Up to 1/12 length on all timbers & planks	Up to 1/6 length on all timbers & planks	Up to 1/3 length 2 faces-limited to 1 face on planks
SPLITS:	6" maximum	12" maximum	Splits not to exceed in length the width of the piece

Taken from Rules for the Measurement and Inspection of Hardwood and Cypress
 NHLA Sales Code and Inspection Regulations
 National Hardwood Lumber Association
 Memphis, TN
 901-377-1818